

SRF-610/611/612/613 UHF RFID Tag

SRF-610 White UHF RFID Tag



Spec.

Operating Frequency	860MHz~960MHz
Protocol	EPC Class 1 Gen 2 (ISO18000-6C)
Storage Capacity	128 bits EPC
Dimension	115mm*35mm*0.5mm
Working Temp.	-40°C~85°C

SRF-611 UHF RFID Anti-metal Tag



Spec.

Operating Frequency	902MHz~928MHz
Protocol	EPC C1 G2 (ISO18000-6C)
Storage Capacity	96 bits EPC
Weight	25g
Dimension	82*33.3*9mm
Material	Corrosion resistance, high intensity engineering plastics
Working Temp.	-40°C~85°C
Application	can be pasted on metal surface

SRF-612 UHF RFID Anti-metal Tag (Outdoor)



Spec.

Operating Frequency	902MHz~928MHz
Protocol	EPC Class 1 Gen 2 (ISO18000-6C)
Storage Capacity	96 bits EPC
Dimension	119.7mm*22.5mm*7.3mm
Working Temp.	-40°C~240°C
Storage Temp.	-40°C~85°C
Material	UV resistance, acid and alkali resisting, high intensity engineering-plastics
IP Level	IP65
Application	can be pasted on metal surface

SRF-613 UHF RFID Pottery Tag



Spec.

Operating Frequency	920.5MHz~924.5MHz
Protocol	EPC Class 1 Gen 2 (ISO18000-6C)
Storage Capacity	128 bits EPC
Dimension	24.7*13.8*3.3mm
Working Temp.	-40°C~85°C
Material	UV resistance, acid and alkali resisting, high intensity engineering-plastics
IP Level	IP65
Application	can be embedded into metal

■ SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE